

Uniview 4MP Bullet IP Camera with 2.8mm - 12mm Vari-Focal Motorized Lens (IPC2324SR5-ADZK-G)

Product Images



Short Description

- SKU: IPC2324SR5-ADZK-G
- 4 MP Resolution
- Weather Protection: IP67

- Power Over Ethernet
- 3 Year Warranty
- SD Card Slot
- Human Body Detection

Additional Information

Compatible Wall Mount Bracket	No
Sensor Size	1/3", progressive scan, CMOS
Resolution	4 MP
Lens	2.8 ~ 12mm, AF automatic focusing and motorized zoom lens
Detect	63m (206ft)~270m (885ft)
Observe	25.2m (82.6ft)~108m (354.3ft)
Recognize	12.6m (41.3ft)~54m (177ft)
Identify	6.3m (20.6ft)~27.0m (88.5ft)
Angle of View (H)	103°~ 31°
Angle of View (V)	55°~ 18°
Angle of View (O)	107°~36°
Adjustment angle (Pan)	Pan: 3° ~ 357°
Adjustment angle (Tilt)	Tilt: 0° ~ 90°
Adjustment angle (Rotate)	Rotate: 0° ~ 360°
Shutter	Auto/Manual, shutter time: 1 ~ 1/100000s
Minimum Illumination	Colour: 0.003 Lux @ F1.6 (AGC ON)
Day/Night	IR-cut filter with auto switch (ICR)
Digital Noise Reduction	2D/3D DNR
S/N	>56dB
IR Range (or LED)	Up to 50m (164 ft) IR range
IR Wavelength	850nm
IR On/Off Control	Auto/Manual
Defog	Digital Defog
Wide Dynamic Range	120dB
Video Compression	H.264, H.265, MJPEG, Ultra 265

H.264 code profile	Baseline profile, High profile, Main Profile
Frame Rate	"Main Stream: 4MP (2688*1520), Max 30fps; 4MP (2560*1440), Max 30fps; 3MP (2304*1296), Max 30fps; 1080P(1920*1080), Max 30fps Sub Stream: 4CIF (704*576), Max 30fps; Third Stream: CIF (352*288), Max 30fps"
Bit Rate (min~max)	128 Kbps~16 Mbps
OSD	Up to 4 OSDs
Privacy Mask	Up to 4 areas
Region of Interest	Up to 2 areas
Motion Detection	Up to 4 areas
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2
Smart IR (or Smart Illumination)	Supported
Image Flip	180°, Horizontal, Normal, Vertical
Dewarping	No
HLC	Yes
BLC	Yes
Audio Compression	G.711
Audio Suppression	Yes
Audio Sampling Rate	8KHZ
Edge Storage (SD)	Micro SD, Up to 256GB
Network Storage	ANR
Supported Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL
Compatible Integration	API, ONVIF Profile G, ONVIF Profile S, ONVIF Profile T
Compatible Clients	EZLive, EZStation, EZView
Web Browser Support	Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below Plug-in free live view: Chrome 57.0+, Firefox 58.0+, Edge 16+, Safari 11+
Network Interface	1 RJ45 10/100M Base-TX Ethernet
Built-in Mic	No

Certifications	"CE: EN 60950-1 UL: UL60950-1 FCC: FCC Part 15"
Maximum Power Consumption	9.5 W
Dimensions (Ø x H)	240.3 × 86.4 × 75.6mm (9.5" × 3.4" × 3.0")
Net Weight	1.0kg (2.2lb)
Material	Metal
Operating Conditions	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
Storage Environment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
Surge Protection	6KV
Ingress Protection	IP67